



HS1E Discontinued & Replacement HS1L Part Numbers

HS1E Discontinued Part Number	HS1L Replacement Part Number
HS1E-140KMSR	HS1L-DQ44KMSR-R
HS1E-140KR	HS1L-DQ44KMSR-R
HS1E-140KRP	HS1L-DQ44KMSRP-R
HS1E-140R	HS1L-DQ44KMSR-R
HS1E-140RP	HS1L-DQ44KMSRP-R
HS1E-144KR-G	HS1L-DQ44KMSR-G
HS1E-144KRP-G	HS1L-DQ44KMSRP-G
HS1E-144KRP-R	HS1L-DQ44KMSRP-R
HS1E-144KR-R	HS1L-DQ44KMSR-R
HS1E-144R-G	HS1L-DQ44KMSR-R
HS1E-144RP-G	HS1L-DQ44KMSRP-G
HS1E-144RP-R	HS1L-DQ44KMSRP-R
HS1E-144R-R	HS1L-DQ44KMSR-R
HS1E-240KR	HS1L-DT44KMSR-R
HS1E-240KRP	HS1L-DT44KMSRP-R
HS1E-240R	HS1L-DT44KMSR-R
HS1E-240RP	HS1L-DT44KMSRP-R
HS1E-244KR-G	HS1L-DT44KMSR-G
HS1E-244KRP-G	HS1L-DT44KMSRP-G
HS1E-244KRP-R	HS1L-DT44KMSRP-R
HS1E-244KR-R	HS1L-DT44KMSR-R
HS1E-244R-G	HS1L-DT44KMSR-G
HS1E-244RP-G	HS1L-DT44KMSRP-G
HS1E-244RP-R	HS1L-DT44KMSRP-R
HS1E-244R-R	HS1L-DT44KMSR-R
HS1E-340KR	HS1L-DT44KMSR-R
HS1E-340KRP	HS1L-DT44KMSRP-R
HS1E-340MSR	HS1L-DT44KMSR-R
HS1E-340R	HS1L-DT44KMSR-R
HS1E-340RP	HS1L-DT44KMSRP-R
HS1E-344KMSR-G	HS1L-DT44KMSR-G
HS1E-344KMSR-R	HS1L-DT44KMSR-R
HS1E-344KR-G	HS1L-DT44KMSR-G
HS1E-344KRP-G	HS1L-DT44KMSRP-G
HS1E-344KRP-R	HS1L-DT44KMSRP-R
HS1E-344KR-R	HS1L-DT44KMSR-R
HS1E-344R-G	HS1L-DT44KMSR-G

HS1E Discontinued Part Number	HS1L Replacement Part Number
HS1E-344RP-G	HS1L-DT44KMSRP-G
HS1E-344RP-R	HS1L-DT44KMSRP-R
HS1E-344R-R	HS1L-DT44KMSR-R
HS1E-3KLMRP-2-TK2002	No Replacement
HS1E-3KMRP-1-TK2002	No Replacement
HS1E-3KMRP-2-TK2002	No Replacement
HS1E-40KR	HS1L-DQ44KMSR-R
HS1E-40KRP	HS1L-DQ44KMSRP-R
HS1E-40RP	HS1L-DQ44KMSR-R
HS1E-433KRP-R	No Replacement
HS1E-44KR-G	HS1L-DQ44KMSR-G
HS1E-44KRP-G	HS1L-DQ44KMSRP-G
HS1E-44KRP-R	HS1L-DQ44KMSRP-R
HS1E-44KR-R	HS1L-DQ44KMSR-R
HS1E-44R-G	HS1L-DQ44KMSR-G
HS1E-44RP-G	HS1L-DQ44KMSRP-G
HS1E-44RP-R	HS1L-DQ44KMSRP-R
HS1E-44R-R	HS1L-DQ44KMSR-R
HS1E-7KMBP-1-TK2213	No Replacement
HS1E-840KMSR	HS1L-DT44KMSR-R
HS1E-844KMSR-G	HS1L-DT44KMSR-G
HS1E-844MSR-G	HS1L-DT44KMSRP-G
HS1E-8C-TK2267	No Replacement

Notes:

1. HS1E and HS1L have the same dimension and same mounting orientation.

2. HS1E rention force is 1500N. HS1L retention force is 3000N.

3. HS1E uses HS9Z-A1/A2/A3 actuators. HS1L uses HS9Z-A1S/A2S/A3S actuators.

4. HS1E equipped with 3-5 contacts. HS1L equipped with 6 contacts.

5. HS1E terminal screw is M3.5 type. HS1L terminal screw is M3 type.